

# Medically Approved 500W ATX PC Power Supply

Product # TMPC-500

## Features

- 90-265 VAC universal input
- Active PFC
- Low ripple & noise
- Output over voltage protection
- Short circuit protection on all outputs
- Resettable power shut down
- Low noise cooling fan
- 100% burn-in at 50°C
- 100% Hi-pot tested
- MTBF > 150,000 hours @25°C
- Line input fuse protection
- Approved to UL 60601-1, IEC 60601-1, EN 60601-1 medical standards
- Complies with EN 61000-3-2, EN 60601-1-2, EN 55011 standards
- < 90µA @264VAC low leakage version available



5.91" X 5.51" X 3.39"  
(150 X 140 X 86 mm)

**\*90-265 VAC universal input + PFC**  
**\*Unit without on/off switch is optional.**

## Input Specifications

- Input voltage: 90 to 265 VAC
- Input frequency: 47 to 63 Hz
- Input current: 8.0A@115VAC, 4.0A@230VAC

## Other Specifications

- Hold-up time: 20ms @115VAC/60Hz, 20ms @230VAC/50Hz.
- Efficiency: 68% @ full load
- MTBF: >200,000 hours at full load @25°C
- Operating temperature: 0°C to +50°C
- Storage temperature: -20°C to +80°C
- Relative humidity: 5% to 95% non-condensing

## Output Specifications

- Over voltage protection: +3.7V to +4.5V for +3.3V; +5.7V to +6.5V for +5V; +13.3V to +15.6V for +12V
- Short circuit protection: On all outputs

| DC Output Voltage | Minimum Load | *Maximum Load | Load Regulation | Ripple & Noise P-P (Max.) |
|-------------------|--------------|---------------|-----------------|---------------------------|
| +3.3V             | 0.5A         | 30A           | ±5%             | 50mV                      |
| +5V               | 0.3A         | 30A           | ±5%             | 50mV                      |
| +12V (1)          | 1A           | 17A           | ±5%             | 120mV                     |
| +12V (2)          | 1A           | 17A           | ±5%             | 120mV                     |
| -12V              | 0A           | 0.8A          | ±10%            | 120mV                     |
| +5Vsb             | 0A           | 2A            | ±5%             | 50mV                      |
| -5V               | 0A           | 0.3A          | ±10%            | 100mV                     |

\*+3.3V & +5V total output: 200W max.

\*+3.3V & +5V & +12V total output: 480W max.

-06/2010-

**Tumbler Technologies + TRUMPower**

Santa Clara, California, USA • Phone: 408-988-6616 • sales@TRUMPower.com • [www.TRUMPower.com](http://www.TRUMPower.com)