

## TRM15 Series



### FEATURES

- 90~264VAC universal input
- Interchangeable plugs available (kit sold separately)
- Single 10~15W, 3~27 VDC output
- Compliant with CEC efficiency level IV regulations

### SPECIFICATIONS

Input Voltage Range.....90~264VAC  
 Input Current (rms).....0.5A Max.  
 Efficiency.....75% typ. at full load  
 Up to 79% for CEC compliant models  
 Standby Power.....< 0.3W @ no load for CEC compliant models  
 Output Voltage.....3V ~ 27V, factory preset  
 Voltage Regulation.....±5% Max.  
 Leakage Current.....0.1mA Max.  
 Operating Temperature.....0°C ~ 40°C  
 Storage Temperature.....-20°C ~ 85°C  
 Operating Humidity.....20% to 90% RH  
 Protections.....OVP, OLP, SCP  
 Safety Standards.....UL/IEC/EN 60601-1, CE, CB, CCC  
 EMC Standards.....EN55011(CISPR11), BSMI, FCC class B  
 Standard Output Connector.....Barrel plug  
 Output Cable / Length..... #18AWG / 4Ft (Desktop)  
 #18AWG / 5Ft (Wall Mount)

### MODEL LIST



Product No.	*Output Voltage	Output Current	Output Wattage	*CEC
TRM15-S03-X	3~5V	3.4~2.0A	10W	IV
TRM15-S05-X	5V~6V	2.0~2.67A	10W	IV
TRM15-S07-X	6V~8V	2.0~1.5A	12W	IV
TRM15-S09-X	8V~11V	1.87~1.36A	15W	IV
TRM15-S12-X	11V~13V	1.36~1.15A	15W	IV
TRM15-S15-X	13V~16V	1.15~0.94A	15W	IV
TRM15-S18-X	16V~21V	0.94~0.72A	15W	IV
TRM15-S24-X	21V~27V	0.72~0.56A	15W	IV

\* Specify output voltage when ordering.

\* Add suffix "G" for CEC compliant models, e.g. TRM15-S19-4G.


\* For output connector options, please consult TRUMPower.

AC Inlet Type	Code X
IEC320/C14	4
IEC320/C6	6
IEC320/C8	8


Wall Mount Plug Type	Code X
US plug	U
EU plug	E
British plug	B
Australian plug	A
Interchangeable	I

### Mechanical Drawing :(mm)

#### Desktop



#### Wall Mount Fixed Plugs



#### Wall Mount Interchangeable Plugs

